

LITEC® 501

four tools in one



LITEC® 400

for extra heavy cable drums



LITEC® 250

small very big



application:

cable rings	●	○	○
vein cables	●	○	○
conduit pipe	●	○	○
defective drums	●	●	●
removable spike	●	●	●

recommendation for:

rings	●	○	○
big drums	●	●	○
small drums	●	●	●

loadable up to:	380 kg	500 kg	190 kg
own weight:	6,8 kg	3,0 kg	1,1 kg
diameter:	500 mm	400 mm	250 mm

cable drum hole diameter:

without spike:	from 13 mm
standard spike:	from 51 mm
LITEC- Lock:	from 45 mm

All application and usage videos
are available on our homepage
on: www.litec-eu.com

Litec Technik für Profis GmbH



Made in Germany

Phone +49 (0)30 93491676 | Fax +49 (0)30 93491673
info@litec-eu.com



Cable dispensers

QUALITY meets INNOVATION



www.litec-eu.com

LITEC® 502

loadable up to 380 kg

optimised hold through
LITEC- Lock

ergonomic carry handle



also for smallest
cable ring diameter



Combines up to four single devices, used for:

- vein cables
- line rings
- conduit pipe
- cable drums of all sizes
- removable spike (with small drum hole from 13 mm)

LITEC® 402

loadable up to 500 kg



LITEC 402 fixated with
usual wood screws
on a big cable drum



honeycomb structure
for additional stability
for the LITEC 402



lug for screw
connection
when required

Use for all cable drum sizes:

- can be mounted on large, heavy cable drums (easy and safe handling)
- extreme stability thanks to honeycomb structure
- ideal for pure drum use
- removable spike (with small drum hole from 13 mm)

LITEC® 252

loadable up to 190 kg



cable drum with
inner diameter
of 13 mm



damaged cable drum
on the LITEC 252



Use for small to medium-sized cable drums:

- ideal for network, fire alarm, solar and antenna cabling
- can be used many times at an attractive acquisition cost
- removable spike (with small drum hole from 13 mm)

Good reasons for all LITEC®- Lock cable dispenser



- optimised hold of the drum **due to LITEC®- Lock**
- with maintenance-free, **dynamic roll-of brake**
- also suitable for **damaged cable drums**
- no relocation necessary
- lightweight, robust and dust-tolerant construction
- modern plastics with high stability
- low own weight

Note:

LITEC®- Lock only usable on units
of the 502, 402, 252 series



www.litec-eu.com